



Visibility in all conditions

Darkness at the workplace is not an issue thanks to the built-in flashlight. Automatic backlight of the display, buttons and rotary switch enables to carry out measurements in all lighting conditions.



Unique design

Using the latest technologies, we have created a compact device for working in the toughest conditions. The rubber housing reduces the effects of liquid pollution and falls (IP67 ingress protection).



Multifunctionality

CMM-30 multimeter provides unique versatility with its 11 basic measurement functions and additional features, including relative measurement, measurement of minimum, maximum and average values or peak value measurement.



Wireless communication

Transfer measurement data via Bluetooth, in „live“ mode, to the **Sone! Multimeter Mobile** application. This allows to record and store the results and include additional description or photos. You can also share measurement data as an e-mail attachment.



Safety and comfort

Sone! CMM-30 meets the safety requirements of CAT III 1000 V / CAT IV 600 V. The ergonomic housing provides a firm grip and convenient function selection – also in protecting gloves.

CAT III

1000 V

CAT IV

600 V

IP67

BLUETOOTH

AUTO BACKLIGHT

BUILT-IN FLASHLIGHT

Technical specifications

Measurement functions	Range	Resolution	Accuracy ±(% m.v. + digits)
AC voltage	up to 1000 V	from 0.001 V	from ±(1.0% m.v. + 5 digits)
DC voltage	up to 1000 V	from 0.1 mV	from ±(0.5% m.v. + 8 digits)
AC / DC current	up to 10.00 A	from 0.1 µA	from ±(1.0% m.v. + 3 digits)
Resistance	up to 60.00 MΩ	from 0.1 Ω	from ±(1.5% m.v. + 5 digits)
Low Z (AC / DC voltage)	up to 1000 V	from 0.001 V	from ±(3.0% m.v. + 5 digits)
Frequency	up to 9.999 kHz	from 0.001 Hz	±(1.0% m.v. + 5 digits)
Capacitance	up to 6000 µF	from 0.01 nF	from ±(3.0% m.v. + 5 digits)
Duty cycle (%)	20.0...80.0%	0.1%	±(1.2% m.v. + 2 digits)
Temperature measurement	-20...+760°C -4...+1400°F	0.1°C 0.1°F	±(1.0% m.v. + 5°C) ±(1.0% m.v. + 9°F)
Continuity / Diode test	✓ / ✓		
Basic features			
Counting		6000 digits	
HOLD		✓	
Manual / automatic range selection		✓ / ✓	
Advanced features			
MIN / MAX / AVG		✓ / ✓ / ✓	
AC+DC measurement		✓	
PEAK HOLD		✓	
Relative measurement REL		✓	
TRMS measurement		✓	
Memory		in mobile application	
Bluetooth communication		✓	
Other features			
Easy access to A / mA fuses		✓ / ✓	
Auto-off		✓	
Empty battery indication		✓	
Integrated flashlight		✓	
Beeper		✓	
Display			
Type		segment-based LCD, 4 digits	
Display backlight		automatic and manual	
Safety and conditions for use			
Measuring category (EN 61010)		CAT IV 600 V CAT III 1000 V	
Ingress protection		IP67	
Dimensions		170 x 75 x 48 mm	
Operating temperature		0...40°C	
Storage temperature		-20...+60°C	

Standard accessories



**Set of test leads
for CMM (CAT IV, M)**
WAPRZCMM2



**Temperature
measurement**

Probe (K-type)
WASONTEMK

Adapter
WAADATEMK



**2x watertight socket
protection plug**



**4x LR03 AAA
1.5 V battery**



**Standard carrying
case**



**Calibration
certificate**



User manual

Optional accessories



Set of test leads

CAT IV, S (for CMM)
WAPRZCMM1

CAT IV (for CMP)
WAPRZCMP1



**Temperature
measurement**

Probe (K-type, bayonet)
WASONTEMP

Probe (K-type, metal)
WASONTEMK2



**Crocodile clip mini,
1 kV 10 A (set)**

WAKROKPL10MINI



**M1 hanging
hook straps**

WAPOZUCH1



**Universal magnetic
hanging strap**

WAPOZUCH6



S1 carrying case

WAFUTS1



**Calibration cer-
tificate issued
by an accred-
ited laboratory**

Check other meters from the CMM family



Sonel CMM-10
WMXXCMM10

- intuitive
- clear reading
- safe and economical
- basic measuring device



Sonel CMM-11
WMXXCMM11

- durable
- versatile
- pocket
- for every electrician



Sonel CMM-60
WMXXCMM60

- ultra-durable
- multi-purpose
- for special applications
- advanced troubleshooting



Sonel CMM-40
WMXXCMM40

- precise
- handy
- extended functionality
- for industry